

IP66

▼ Charaterastic

Effortless Smart Lighting for Cities

- 1.Smart & Efficient: Integrates with smart city systems, offers wide power/color options (100W-300W, 3000K-6000K), and boasts high efficiency (up to 130 lm/W).
 - 2.Durable Design: Modern, high-strength aluminum body (IP66 & IK10) resists impact, dust, and moisture.
 - 3.Advanced Cooling: Dual-cavity system ensures optimal LED performance and lifespan.
 - 4.Precise Light: Professional optics deliver accurate light distribution for safety and comfort.
 - 5.Effortless Upkeep: Tool-free access and adjustable tilt simplify maintenance.
- ✦ Pole mounting.
✦ Working temperature is -50°C to 70°C

▼ Application

✦ Outdoor Occasion such as Urban main road, secondary road, branch road, industrial park road lighting, etc

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI

▼ Technical Data (full sery)

| Model | SIZE (mm) | POWER (W/M) | CRI | CCT (K) | LUMINOUS | VOLT | Control | Beam Angle | PF | N.W |
|------------|--------------|-------------|-----|------------|----------|-------------|---------------|------------|----|----------|
| RL-01A-100 | 519X210X70mm | 100 W | >80 | 2700-6000K | 13500 LM | 100-277V AC | On/Off or Dim | T3M / T4M | 95 | 3.40 kgs |


✦ Notes:
1. Finish: Black, and customized RAL available
2. It has four different size from 100W-300W.

▼ Project




▼ Photos





T3M



T4M