

IP66

▼ Charaterastic

Effortless Smart Lighting for Cities

- 1.Smart & Efficient: Integrates with smart city systems, offers wide power/color options (100W-300W, 3000K-6000K), and boasts high efficiency (up to 130 lm/W).
 - 2.Durable Design: Modern, high-strength aluminum body (IP66 & IK10) resists impact, dust, and moisture.
 - 3.Advanced Cooling: Dual-cavity system ensures optimal LED performance and lifespan.
 - 4.Precise Light: Professional optics deliver accurate light distribution for safety and comfort.
 - 5.Effortless Upkeep: Tool-free access and adjustable tilt simplify maintenance.
- ✦ Pole mounting.
✦ Working temperature is -50°C to 70°C

▼ Application

I ✦ Outdoor Occasion such as Urban main road, secondary road, branch road, industrial park road lighting, etc

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
RL-01B-150	565X250X70mm	150 W	>80	2700-6000K	20250 LM	100-277V AC	On/Off or Dim	T3M / T4M	95	4.00 kgs

I ✦Notes:
1. Finish: Black, and customized RAL available
2. It has four different size from 100W-300W.


▼ Project




▼ Photos



▼ Photometric curve



T3M



T4M