



▼ Characteristic

- 1.Superior Optical Performance
- High-efficiency LED with precise beam control, offering multiple beam angles and color temperatures (2700K/3000K/4000K).
- Glare-free design for uniform and comfortable illumination.
- 2.Durable and Reliable
- Die-cast aluminum housing with corrosion-resistant coating, suitable for indoor and outdoor use.
- IP65/IP67 waterproof and IK08 impact-resistant for long-lasting performance.
- 3.Easy Installation
- Supports recessed, surface-mounted, and wall-mounted options for versatile applications.
- Lightweight design for hassle-free installation.
- 4.Smart Control
- Compatible with DALI, DMX512, and 0-10V for dimming and dynamic lighting effects.
- Sensor integration available for intelligent energy-saving solutions.

▼ Application

I³Architectural façades, Landscape lighting, Commercial spaces, and Residential settings etc.



ON/OFF 0-10V DALI DMX TRIAC

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available,
Pls confirm before ordering.

▼ Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WL-02B-30	L155xW145xH97	30 W	/	3000K-5700K	82 LM/W	5/10/15/30/60°	AC220V	DMX512	/	Down
WL-02B-36	L155xW145xH97	36 W	> 80	Chromatic (RGB)	45 LM/W	5/10/15/30/60°	AC220V	ON/OFF	/	Down
WL-02B-54	L155xW145xH97	54 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/60°	AC220V	DMX512	/	Down

- I+Notes:
1. Finish: Black, and customized RAL available
2. It has four size with 4 different watt from 10W-48W.

▼ Simulation



▼ Project



▼ Photometric curve

