

▼ Characteristic



1. Precise Optics
 - Advanced lens and reflector system with customizable beam angles (e.g. 5°, 10°, 30°, 60°).
 - Uniform illumination with minimal glare.
2. Flexible Customization
 - Multiple mounting options and accessories (anti-glare shields, honeycomb louvres).
 - Dimmable and smart system compatible (e.g., DALI, DMX512).
3. Durable Build
 - IP66-rated for water/dust resistance, IK08 impact protection.
 - Operates reliably in -20°C to +40°C environments.
4. Energy Efficient & Eco-friendly
 - High-efficiency LEDs with 50,000+ hours lifespan.
 - Modular, recyclable design with low energy consumption.
5. Versatile Applications
 - Perfect for facades, bridges, landscapes, and commercial spaces.
 - Adjustable lighting effects for diverse project needs.



IP66 ▼ Application

Outdoor Occasion such as Building Facades, Bridges, Gardens and Green Spaces, Landmark Features, Commercial Areas, Water Features, Theme Parks and Entertainment Facilities, Urban Streetscapes, Airports and Stations, Sports Venues and etc.

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



Mono



Tunable White



RGB



RGBW

ON/OFF

0-10V DALI

▼ Family Matrix (Three sizes)



FL-11A-36



FL-11B-36



FL-11C-36

▼ Simulation



▼ Project




▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
FL-11A-36	L175xW145xH155mm	36 W	> 80	3000K-5700K	120 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	ON/OFF	/	Standard 1m cable
FL-11A-54	L175xW145xH155mm	54 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable
FL-11A-72	L175xW145xH155mm	72 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable
FL-11B-36	L155xW145xH125mm	36 W	> 80	3000K-5700K	120 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	ON/OFF	/	Standard 1m cable
FL-11B-54	L155xW145xH125mm	54 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable
FL-11B-72	L155xW145xH125mm	72 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable
FL-11C-36	L155xW145xH620mm	36 W	> 80	3000K-5700K	120 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	ON/OFF	/	Standard 1m cable
FL-11C-54	L155xW145xH620mm	54 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable
FL-11C-72	L155xW145xH620mm	72 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/10 X30/10X60°	AC85-265V	DMX512	/	Standard 1m cable

I+Notes:

1. Finish: Black, and customized RAL available
2. It has three different sizes from 36W-72W.

▼ Photometric curve



▼ Naming scheme

