



▼ 2020



▼ Characteristic

1. Eco-Friendly Optical-Grade Silicone

-Crafted with high-transparency, optical-grade silicone that is environmentally friendly and engineered for exceptional durability. It offers strong resistance to salt, acids, alkalis, UV exposure, and flames—ideal for harsh outdoor conditions.

2. Flexible Form, Perfect Fit

-Innovative free-bending structural design enables seamless application across a variety of curved architectural surfaces. Designed to deliver uniform and smooth wall washing effects without light breakpoints.

3. IP67 Seamless Waterproofing

-Built with an integrated extrusion molding process to ensure consistent waterproof performance. Rated IP67 for long-term reliability in outdoor environments.

4. Patented Optical System

-Equipped with a proprietary lens design offering multiple beam angle options to suit different lighting requirements—precise, efficient, and visually refined.

5. Concealed End Cap Design

-A minimalist hidden end cap ensures a clean visual finish. Tool-free installation design supports rapid and secure mounting.

▼ Application

► **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel

► **Urban:** Administrative Building , Commercial Building , Hotel , Mall

► **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available,
PIs confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data

| Model | SIZE (mm) | BENDING DIRECTION | POWER (W/M) | CRI | CCT (K) | LUMINOUS (LM/M) | Beam angle | VOLT | CUTTING (mm) | Control Mode |
|------------------|-----------|-----------------------|-------------|-----|--------------------------|-----------------|---|-------|--------------|--------------|
| FlexWash-06_2020 | W20xH20mm | 3D Bending (Φ>400mm) | 18 | >80 | Mono 2700-6500K | 1350~1800 | 15°, 20°, 30°,45°,20x30°,20x36°,25x45°,20x55° | DC24V | 41.5 | ON/OFF |
| FlexWash-06_2020 | W20xH20mm | 3D Bending (Φ>400mm) | 24 | >80 | Tunable White 2700-6500K | 1950 | 15°, 20°, 30°,45°,20x30°,20x36°,25x45°,20x55° | DC24V | / | ON/OFF |


| | | | | | | | | | | |
|------------------|-----------|----------------------|----|---|-------------------|-----|---|-------|---|--------|
| FlexWash-06_2020 | W20xH20mm | 3D Bending (Φ>400mm) | 24 | / | Chromatic (RGB) | 750 | 20°, 30°, 45°, 20x30°, 20x36°, 25x45°, 20x55° | DC24V | / | ON/OFF |
| FlexWash-06_2020 | W20xH20mm | 3D Bending (Φ>400mm) | 24 | / | Chromatic (RGB+W) | 880 | 20°, 30°, 45°, 20x30°, 20x36°, 25x45°, 20x55° | DC24V | / | ON/OFF |

Notes:


1. Finish: White, and customized Black, Grey available
2. It has six different sizes from 15W-48W.

▼ Installation Method


Surface Mounted




▼ Outlet Method



Bottom Outlet







Straight Outlet





Side Outlet


▼ Photometric curve




▼ Accessories




Mounting clip




Aluminum profile




Aluminum flexible profile



Stainless steel flexible chain



Flex Aluminum profile with shield





Bottom outlet

4

5

6

▼ Project of Flex Wall Washer



FlexWash-03D-48

FlexWash-03D-36

FlexWash-03D-48

FlexWash-03D-48



